

MCHP LP

Varnished steel frame



Shock absorbers

Water inlet 3/4" M



(three phase)



(single phase)



(three phase)

Standard equipment:


- Header tank
- Plastic covers



- Brass head pump with total stop system



- Integrated elastic joint, for best pump coupling (three phase model).



- Stackable up to four machines with kit 4 spacer code 6.608.0031 (OPTIONAL)

Stainless steel frame version:

- 8.626.0005 MCHPX 1211 LP
- 8.626.0006 MCHPX 1515 LP
- 8.626.0007 MCHPX 2015 LP
- 8.626.0008 MCHPX 2021 LP

Optional:

- Wall mount supports code 6.608.0030

VERSION
60 Hz
AVAILABLE
DETAILS PAGE 9

	MCHPV 1211 LP	MCHPV 1515 LP	MCHPV 2015 LP	MCHPV 2021 LP
Code	8.626.0001	8.626.0002	8.626.0003	8.626.0004
operat. pressure/max	30±120 bar/max 150	30±150 bar	30±200 bar	30±200 bar
operat. pressure/max	435±1740 psi/max 2175	435±2175 psi	435±2900 psi	435±2900 psi
delivery rate	345÷660 l/h	450÷900 l/h	450÷900 l/h	630÷1260 l/h
delivery rate	1.52÷2.91 GPM	1.98÷3.96 GPM	1.98÷3.96 GPM	2.77÷5.55 GPM
abs. power/voltage	3000W - 230V~50Hz 1 ph	5000W - 400V~50Hz 3 ph	7000W - 400V~50Hz 3 ph	9400W - 400V~50Hz 3 ph
Motorpump type	MP3	MPW5	MPW5	MPW5
RPM	1450 RPM	1450 RPM	1450 RPM	1450 RPM
detergent tank	-	-	-	-
inlet max temperature	40 °C	40 °C	40 °C	40 °C
machine dimensions	75x50x35 cm	75x50x35 cm	75x50x35 cm	75x50x35 cm
machine weight	40 Kg /88 lbs	45 Kg /99 lbs	50 Kg /110 lbs	55 Kg /1121 lbs